

Article datasheet

Flexible Light Pipe with LED green

Article-No.: 063.63.305

Manufacturer: BIVAR
Manufacturer article-no.: FLPV12.0-UG



Image may be similar

Color: Green
Model: Flexible Plug-On Adapter
Weight: 2g
Conformities:

Reach COMPLIANT

RoHS COMPLIANT

SVHC COMPLIANT



You can find all information on the web on our article detail page

Would you like individual advice?
We look forward to your email to products@ettinger.de.

Subject to change and errors.

ITEM	QTY	PART NUMBER	PART DESCRIPTION
1	1	FLPV-XX	Flexible Light Pipe Adapter/Vertical, w/LED, See page 2 & 3
2	1	LC-XX-X	Flexible Light Pipe Lens Cap Assembly

* L **	Tolerance
1.0" ~ 16.0"	±0.050"
16.1" ~ 40.0"	±0.15"
40.1" ~ 80.0"	±0.30"
80.1" ~ 3,940.0"	±0.5%

Available in 0.1" increments only

Technical drawing of the Flexible Light Pipe with LED green component, showing dimensions and recommended mounting holes.

Dimensions:

- L= 304.8mm
- 0.025 [0.6mm]
- 0.320 [8.1mm]
- 0.240 [6.1mm]
- 0.210 [5.3mm]
- 0.100 [2.5mm]
- 0.495 [12.6mm]
- 0.145 [3.7mm]

Recommended Mounting Holes:

- Ø.128^{+0.003}_{-.002}

ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

- REVERSE VOLTAGE: 5V
- REVERSE CURRENT: 100µA
- OPERATING TEMPERATURE RANGE: -20° C ~ 80° C
- STORAGE TEMPERATURE: -30° C ~ 150° C
- LEAD SOLDERING TEMPERATURE(15" FROM BODY): 260° C FOR 5 SECONDS

RECOMMENDED FOOTPRINT:

- Ø.032^{+0.003}_{-.002}
- 0.100 [2.5mm]